

FREQUENCY RANGE: 2-6GHz

Broadband Low Noise Amplifiers

MWA 02060-2025	20	1.0	2.0	+12	+22	2.0:1	+12/100
MWA 02060-3025	30	1.0	2.0	+12	+22	2.0:1	+12/120
MWA 02060-4025	40	1.0	2.0	+12	+22	2.0:1	+12/200
MWA 02060-3020	30	1.0	2.0	+14	+24	2.0:1	+12/150

Broadband Amplifiers

MWA 02060-2004	20	1.0	4.0	+15	+22	2.0:1	+12/80
MWA 02060-3004	30	1.0	4.0	+15	+22	2.0:1	+12/140
MWA 02060-4004	40	1.0	4.0	+15	+22	2.0:1	+12/200
MWA 02060-2035	20	1.0	3.0	+15	+22	2.0:1	+12/800

Broadband Medium Power Amplifiers

MWA 02061-2020	20	1.0	5.0	+20	+30	2.0:1	+15/220
MWA 02061-3020	30	1.25	5.0	+20	+30	2.0:1	+15/260
MWA 02061-4020	40	1.5	5.0	+20	+30	2.0:1	+15/300
MWA 02061-3023	30	1.25	5.0	+23	+33	2.0:1	+15/300
MWA 02061-3025	30	1.25	6.0	+25	+35	2.0:1	+15/600
MWA 02061-4027	40	1.5	6.0	+27	+37	2.0:1	+15/700
MWA 02061-3530	35	1.5	6.0	+30	+40	2.0:1	+15/1300

1. Parameters are guaranteed at +25°C (case temperature)
2. Case outline drawing (see page 1-22)